

# TWN4 MULTITECH 2 LF HF

## PROGRAMMABLE RFID READER/WRITER FOR LF/HF/NFC



TWN4 MultiTech 2 LF HF  
(inlay customizable)

ELATEC's TWN4 family of RFID readers and writers allows users to read and write to almost any 125 kHz and 13.56 MHz tags and/or labels. It supports all major transponders from various suppliers like ATMEL, EM, ST, NXP, TI, HID etc. and ISO standards like ISO 14443A/B (T=CL), ISO 15693, ISO 18092 / ECMA-340 (NFC).

The TWN4 MultiTech 2 LF HF reader has integrated RFID (LF & HF) and NFC, which is supported by mobile phones with Android version 4.3 or greater. The app on the reader communicates with the NFC module with easy commands.

### Special features:

- + Powerful SDK for writing apps which are executed directly on the reader
- + Firmware update in the field possible
- + On-board 18 kB flash storage, e.g. for storing user accessible non-volatile data
- + Direct chip-commands support
- + Two on-board SAM sockets (Secure Access Module)
- + CCID and PC/SC 2.01
- + 4 GPIOs
- + Supports quick (re)configuration over network and over wireless interface with TWN4 CONFIG Card
- + TWN4 Upgrade Card for P and PI options available on request
- + 3D construction data (STEP) available on request



Elevator



EV Chargers



Access



Shop POS



Fitness  
Equipment



Ticket POS



PC Log-on



Document  
Management



Driver ID



Vending



Parking



Gaming



Locker Locks



Time  
Attendance



Industrial  
PC

### TECHNICAL DATA

FREQUENCY	125 kHz (LF) / 13.56 MHz (HF)
ANTENNA(S)	Integrated
HOUSING	Material: ABS UL94-V0, color: black or white
DIMENSIONS (L X W X H)	88 mm x 56 mm x 18 mm / 3.5 inch x 2.2 inch x 0.7 inch
POWER	4.3 V - 5.5 V via USB; via generic interface (X1) 3.3 V ± 5%; RS-232 requires 5 V external power supply Limited power source according to the safety norms listed in the respective declaration of conformity, short-circuit current < 8 A
POWER OUTPUT	125 kHz: -10.01 dbμA/m @ 10 m 13.56 MHz: -2.25 dbμA/m @ 10 m
MODULATION	ASK / ASK
CURRENT CONSUMPTION	RF field on: 120 mA typically / Sleep: 500 μA typ. / Cyclic Operation: TBD
TEMPERATURE RANGE	Operating: -25 °C up to +70 °C (-13 °F up to +158 °F) Storage: -45 °C up to +75 °C (-49 °F up to +167 °F)
RELATIVE HUMIDITY	5% to 95% non-condensing
READ- / WRITE DISTANCE	LF and HF: Up to 100 mm / 4 inch, depending on environment and transponder
OPERATING MODES (USB)	USB keyboard emulation – USB virtual COM port – CCID / PC/SC 2.01
MTBF	500,000 hours
WEIGHT	Approx. 117 g / 4.13 oz (with cable)
SUPPORTED TRANSPONDERS (STANDARD) 13.56 MHZ	<u>ISO14443A:</u> LEGIC Advant <sup>1)</sup> , MIFARE Classic EV1 <sup>2)</sup> , MIFARE Classic, MIFARE Mini, MIFARE DESFire EV1, MIFARE DESFire EV2 <sup>3)</sup> , MIFARE DESFire Light <sup>4)</sup> , MIFARE Plus S, X, MIFARE Pro X <sup>5)</sup> , MIFARE Smart MX <sup>5)</sup> , MIFARE Ultralight, MIFARE Ultralight C, MIFARE Ultralight EV1 <sup>2)</sup> , NTAG2xx, SLE44R35 <sup>5)</sup> , SLE66Rxx (my-d move) <sup>5)</sup> , Topaz <u>ISO18092 ECMA-340:</u> NFC Forum Tag 1-5, NFC Peer-to-Peer, Sony FeliCa <sup>6)</sup> , NFC Active and passive communication mode <u>ISO14443B:</u> Calypso <sup>5)</sup> , Calypso Innovatron protocol <sup>5)</sup> , CEPAS <sup>5)</sup> , HID iCLASS <sup>1)</sup> , Moneo <sup>5)</sup> , Pico Pass <sup>7)</sup> , SRI4K, SRIX4K, SRI512, SRT512 <u>ISO15693:</u> EM4x33 <sup>5)</sup> , EM4x35 <sup>5)</sup> , HID iCLASS <sup>1)</sup> , HID iCLASS SE/SR <sup>1)</sup> , ICODE SLI, LEGIC Advant <sup>1)</sup> , M24LR16/64, MB89R118/119, SRF55Vxx (my-d vicinity) <sup>5)</sup> , Tag-it, PicoPass <sup>7)</sup>
SUPPORTED TRANSPONDERS (STANDARD) 125 KHZ <sup>8)</sup>	AWID, Cardax <sup>9)</sup> , CASI-RUSCO, Deister <sup>9)</sup> , EM4100, 4102, 4200 <sup>10)</sup> , EM4050, 4150, 4450, 4550, EM4305 <sup>11)</sup> , FDX-B <sup>12)</sup> , EM4105 <sup>12)</sup> , UltraProx <sup>12)</sup> , HITAG 1 <sup>13)</sup> , HITAG 2 <sup>13)</sup> , HITAG S <sup>13)</sup> , ICT <sup>4)</sup> , IDTECK, Isonas, Keri, Miro, Nedap <sup>9)</sup> , PAC <sup>4)</sup> , Pyramid, Q5, T5557, T5567, T5577, TIRIS/HDX <sup>12)</sup> , TITAN (EM4050), UNIQUE, ZODIAC
SUPPORTED TRANSPONDERS (OPTION P)	All Standard Transponders, Cotag, G-Prox <sup>9)</sup> , HID DuoProx II, HID ISO Prox II, HID Micro Prox, HID ProxKey III, HID Prox, HID Prox II, Indala, ioProx, Nexwatch
SUPPORTED TRANSPONDERS (OPTION PI)	Requires TWN4 SIO Card, All Standard Transponders, All Option P Transponders, HID iCLASS, HID iCLASS SE/SR/Elite, HID iCLASS SEOS (Facility Code/PAC) <sup>14)</sup>
OS SUPPORT	Windows Embedded CE <sup>4)</sup> , 7 (32-/64-bit), 8, 8.1, 10, Linux, Android <sup>4)</sup> , iOS <sup>4)</sup> , MAC OS X <sup>4)</sup>
PERIPHERAL INTERFACES	USB, RS-232, TTL serial (logic level 3.3 V, CMOS, 5 V tolerant), I <sup>2</sup> C, 4 GPIOs, Clock/Data, Wiegand
TRANSMISSION SPEED	Host: USB Full speed (12 Mbit/s), RS-232: up to 115,200 baud, HF Air: up to 848 kbit/s
CERTIFICATION NAME	TWN4 MultiTech 2 LF HF
CERTIFICATION(S)	CE/RED, FCC, IC, REACH and RoHS-III compliant, and many more <sup>15)</sup>

<sup>1)</sup>UID only <sup>2)</sup>r/w enhanced security features on request <sup>3)</sup>EV2/EV3 supported as part of the EV1 downward compatibility <sup>4)</sup>On request <sup>5)</sup>r/w in direct chip command mode <sup>6)</sup>UID + r/w public area <sup>7)</sup>UID only, read/write on request <sup>8)</sup>125 kHz technology requires a Russian local test and import license from the ministry of Trade and Industry (MINPROMTORC). This license has to be in place before Elatec can accept any order to be shipped to Russia <sup>9)</sup>Hash value only <sup>10)</sup>Only emulation of 4100, 4102 <sup>11)</sup>From FW V4.05 <sup>12)</sup>134.2 kHz only <sup>13)</sup>Without encryption <sup>14)</sup>UID + PAC (Facility Code), r/w on request <sup>15)</sup>More information on request

ORDER CODE(S)	T4BT-FB2BEL6	USB BLACK
	T4BT-FB2WEL6	USB WHITE
	T4BT-FR2BEL6	RS-232 BLACK
	T4BT-FR2WEL6	RS-232 WHITE
	T4BT-FB2BEL6-P	USB OPTION P BLACK
	T4BT-FB2WEL6-P	USB OPTION P WHITE
	T4BT-FR2BEL6-P	RS-232 OPTION P BLACK
	T4BT-FR2WEL6-P	RS-232 OPTION P WHITE
	T4BT-FB2BEL6-PI	USB OPTION PI BLACK
	T4BT-FB2WEL6-PI	USB OPTION PI WHITE
	T4BT-FR2BEL6-PI	RS-232 OPTION PI BLACK
T4BT-FR2WEL6-PI	RS-232 OPTION PI WHITE	

## ACCESSORIES

HOLDER(S)	HKSI-B	Snap-In Holder black
	HKSI-W	Snap-In Holder white
	HKBR-B	Bracket Holder black
	HKBR-W	Bracket Holder white
POWER SUPPLY	PWA-EU3	Power Supply (EU)
	PWA-US3	Power Supply (US)
	PWA-UK3	Power Supply (UK)
	PWA-JP3	Power Supply (JP)
CABLES	CAB-B2	USB cable type A 200 cm / 78.74 inch
	CAB-B3	USB cable type A 12 cm / 4.72 inch
	CAB-B4	USB cable type A 45 cm / 17.72 inch
	CAB-B7	USB cable type A 120 cm / 47.24 inch
	CAB-M1	USB cable mini 12 cm / 4.72 inch
	CAB-M2	USB cable mini 25 cm / 9.84 inch
	CAB-R2	RS-232 cable 200 cm / 78.74 inch

### ELATEC GmbH

Zeppelinstr. 1  
82178 Puchheim  
Germany  
P +49 89 552 9961 0  
F +49 89 552 9961 129  
E-Mail: info-rfid@elatec.com  
Website: elatec.com

### ELATEC Systems GmbH

Schwieberdinger Str. 44  
71636 Ludwigsburg  
Germany  
P +49 7141 309736 0  
E-Mail: info-rfid@elatec.com  
Website: elatec.com

### ELATEC Inc.

1995 SW Martin Hwy  
Palm City • FL 34990  
USA  
P +1 772 210 2263  
F +1 772 382 3749  
E-Mail: americas-info@elatec.com  
Website: elatec.com

### ELATEC Technology (Shenzhen) LLC

918, Main Building, Tian An Cyber Times  
Tower, No. 6, Tairan Fourth Road, Tian 'an  
Community, Shatou Neighborhood  
Futian District • Shenzhen • China  
P/F +86 755 2394 6014  
E-Mail: apac-info@elatec.com  
Website: elatec.com

ELATEC reserves the right to change any information or data in this document without prior notice. ELATEC declines all responsibility for the use of this product with any other specification but the one mentioned above. Any additional requirement for a specific customer application has to be validated by the customer himself at his own responsibility. Where application information is given, it is only advisory and does not form part of the specification. Disclaimer: All names used in this document are registered trademarks of their respective owners.